



Multifak® EP

Automotive Wheel Bearing & Chassis Grease

Product Data Sheet

Customer benefits

- **Protects metal surfaces**
Effective EP additive protects against component wear under high load conditions. Rust and corrosion inhibitors protect metal surfaces.
- **Resist oxidation**
Formulated with antioxidants to resist oxidation to enhance grease service life.
- **Reduces complexity**
Multipurpose capability allows use in a wide range of industrial and automotive applications reducing the number of different greases required and eliminating product misapplication.

Applications

Can include;

- Automotive wheel bearings
- Chassis grease point lubrication
- Industrial plain and rolling element bearings
- General plant lubrication
- Centralized lubrication systems (NLGI 1)
- Construction equipment bearings
- Earthmoving, quarrying and mining
- Agricultural equipment

Usable temperature range in continuous service is:

- NLGI 1 -25 to 120°C
- NLGI 3 -20 to 120°C

Product features:

Multipurpose EP grease contains highly refined mineral base oils, lithium thickener, extreme pressure (EP) additives and rust and oxidation inhibitors. Suitable as a multipurpose automotive grease for general purpose applications..

A Chevron company product

All trademarks are property owned by Chevron Africa-Pakistan Services (Proprietary) Limited or Chevron Intellectual Property LLC and licensed to Astron Energy Proprietary Limited.



Product specifications

MULTIFAK EP KEY PROPERTIES	RESULTS	
NLGI Grade	1	3
Product Code	540811	540813
Dropping Point, °C	195	205
Oil Viscosity		
mm ² /s @ 40°C	200	200
mm ² /s @ 100°C	17.5	17.5
Penetration, Worked @ 25°C	325	235
Thickener (Lithium), m %	6	10
Timken OK Load, kg	18	18

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by Chevron Lubricants; Africa, Middle East and Pakistan.

Environment, Health and Safety Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal. To obtain a MSDS for this product, visit www.caltexoils.com.

For more information, go to www.chevronlubricants.com

A Chevron company product

All trademarks are property owned by Chevron Africa-Pakistan Services (Proprietary) Limited or Chevron Intellectual Property LLC and licensed to Astron Energy Proprietary Limited.

MLTIFK EP/SA/PDSv3_07/06/2018

© 2018 Chevron Lubricants used under license. All rights reserved.